

# Easy Solar Kit



Balcony

## Balcony Air Vertical

TSOL-ESK400-Air(V) / TSOL-ESK800-Air(V)



Product  
Warranty

- Lightweight
- All in one Design
- Highly Waterproof
- Wind Prevention
- Plug & Play
- Built-in WiFi, APP Remote Monitoring
- Output Power 400W/800W  
Can be Adjusted According to  
Local Regulations



TSUNESS Co., Ltd

sales@tsun-ess.com www.tsun-ess.com +86-512-66186028

# Technical Data

Model	TSOL-ESK400-BA	TSOL-ESK800-BA
<b>PV Module Parameter *</b>		
Module Power(Pmpp @STC)	200 * 2	200 * 4
Max. Module Efficiency	20.4%	20.4%
Temp. Coef. (Power)	-0.34%/°C	-0.34%/°C
Color	Black	Black
<b>AC Output Parameter</b>		
Max. System Continuous Output Power (W)**	400	800
Max. Output Current (A)	2	4
Nominal Output Voltage (V)***	220/230/240	
Nominal Frequency (Hz)***	50/60	
Power Factor	>0.99	
Output Current Harmonic Distortion	<3%	
Length of AC End Cable***	5m (10m, 15m optional)	
<b>Certification</b>		
Solar Module	CE,TUV,UL,CQC,IEC 61215,IEC 61730	
Microinverter	CE-LVD,CE-EMC,CE-RED,VDE 4105,EN 50549-1	
Bracket	EN 10204:2017, EN 1090-1:2009+A1: 2011	
<b>Environmental Parameter</b>		
Environmental Protection Rating	IP67	
Operating Ambient Temperature Range	-25 °C to 65 °C	
Relative Humidity	0-100%	
Max. Operating Altitude Without Derating [m]	2000	
<b>Mechanical Parameter</b>		
Weight [kg]	13	25
Package Dimensions (W×H×D mm)	1340*960*65	1340*960*65 *2pcs
Warranty	12 years	

\* The colour , brand and power of the solar module can be customized if the PV module is compatible to ESK system.

\*\* The output power of the system can be limited to according to local regulations.

\*\*\* The AC voltage , frequency range and plug type may vary depending on specific country grid.

## Standard Configuration



Lightweight (3.4kg)

200W PV Module



DC Cable  
(2m, Only for ESK800)

AC End Cable (5m)



Microinverter

## System Diagram

